

Locking Barrel Connectors

Fact Sheet



Locking Barrel Connectors have an innovative twist and lock design allowing for more efficient wire connecting. No stripping of wires required; simply insert the wires and twist 90°, locking the wires into place.

DESCRIPTION:

- Moisture resistant construction
- Will not deteriorate from exposure to water, oxidation, rust, chemicals
- Connects to wire without removal of any wire jacket or insulation
- Works with multiple wire gauges from 10 to 14
- Provides a tightly locked connection, impervious to fill replacement

INSTALLATION:

1. To assist with strain relief, twist wires together approximately 8" from the connector
 2. DO NOT strip jacket from wire
 3. Connector is gauge specific; Verify wire gauge matches connector gauge
 4. Insert wires into holes fully so they are visible in the clear cap
 5. Twist connector closed until locked
- Do not use with THHN/THWN or any stranded wire product.
 - Do not pull on wires after connection is made.



Installation
Video

Options & Add-Ons



PRO-TRACE® HDD-CCS
45 / 50 MIL HDPE TRACER WIRE



PRO-TRACE® HF-CCS
30 / 45 MIL HDPE TRACER WIRE



PRO-TRACE® HS-CCS
30 / 45 MIL HDPE TRACER WIRE



COPPER
30 / 45 MIL HMWPE TRACER WIRE